

FAMOUS BULTACO

There is much more to these machines than their just being "Cute little things".

In spite of all efforts to look like a street bike, the Lobitos MK4 are simply trail, woods, and enduro bikes, evidenced by their knobby front and rear tires, small light brakes and the ability to lug a large body up and down the trails.

Enjoyment is the key word to trail riding, whether it be serious competition enduro, or just rounding-up-the-cows.

The fine handling, the high torque and the 5 speed gearbox are some of the features that help achieve this enjoyment, and at times when you may become entrapped in a difficult situation you will get the feeling that the machine is thinking for you.



HANDLING

Lobito Mk4 125

MK4 125 cc. 2 stroke 51.5 x 60 mm, 124.98 cc. 14:1

Bore and

Number of cylinders Cycle Bore and stroke Displacement Compression ratio

SPECIFICATIONS

ENGINE

Alloy cylinder head and alloy cylinder with hardened liner

Compression ratio
Brake horsepower

AMAL 625

18.4 at 8500 rpm.

Electronic System with battery

5 speeds 1. 0.287:1 - II. 0.442:1 - III. 0.625:1 - IV. 0.821:1 - V. 1:1

Multiple plates in oil bath

3/8" Chain (ASA 2035) 1/2" Chain (ISO-42) with tensioner

Telescopic with hydraulic dampening 6 1 , " travel (165 mm.) Swinging arm with hydraulic dampening 3 3/1 " travel (94 mm.)

 2.50×21 " Knobby tyre 3.50×18 " Knobby tyre

140 x 35 mm. (9600 mm²) 140 x 40 mm. (11360 mm²)

73 mph. (118 Kms/h.) 1.98 U. S. gallons (7.5 lts.) 51.02" 75.83" 41.62" x 32.48" 31.89" 12.5" 13.81" 227 lbs. (103 kgs.) CARBURETOR

IGNITION

GEARBOX

Ratios

CLUTCH

TRANSMISSION

Primary drive Rear drive

SUSPENSION

Front suspension Rear suspension

Front wheel

Rear wheel

BRAKE!

Front brake diameter & width Rear brake diameter & width

GENERAL

Cruising speed
Gas-tank capacity
Wheelbase
Overall length
Handlebars, weight and width
Saddle height
Ground clearance

Foot-rest height Empty weight 2 stroke 60.5 x 60 mm. 174.77 cc. 12:1 22 at 8000 rpm.

Lobito Mk4 175

MK4 175 cc.

AMAL 930

Electronic System with battery

5 speeds

1. 0.287:1 - II. 0.442:1 - III. 0.625:1 - IV. 0.821:1 - V. 1:1

Multiple plates in oil bath

3/8" Chain (ASA 2035) 1/2" Chain (ISO-42) with tensioner

Telescopic with hydraulic dampening 6 1, " travel (165 mm.) Swinging arm with hydraulic dampening 3 2,4" travel (94 mm.)

 $2.50 \times .21$ " Knobby tyre 3.50×18 " Knobby tyre

140 x 35 mm. (9600 mm²) 140 x 40 mm. (11360 mm²)

75 mph. (120 Kms/h.) 1.98 U. S. gallons (7.5 lts.) 51.02" 75.83" 41.62" x 32.48" 31.89" 12.5" 13.81" 231 lbs. (105 kgs.)





MOTORCYCLES UNLIMITED 203 SO. CENTRAL ROXANA. ILL. 62084 PHONE 254-7081

COMPAÑIA ESPAÑOLA DE MOTORES, S. A. - San Adrián de Besós - Barcelona - SPAIN